

ROLLER TRAILERS

Earning a superior rating by boat users Venture roller trailers are excellent for boaters who load and launch more frequently. Venture manufactured rollers are preferred because they are accommodating and manageable.

Model	Tire Size	Load Cap.	Overall Boat Width	Boat Length	Frame Size	Between Fender Width	# of Rollers	Coupler Size	Brakes & Tongue Jack
SINGLE AXLE ROLLER 1550-2450 Load Capacity									
VR-1550	5.30 x 12 LRC 5H	1550	78"	14'-15"*	2x3	60"	12	2"	Optional
VR-1850	5.30 x 12 LRD 5H	1850	78"	15'-16"*	2x3	60"	12	2"	Optional
VR-2050	St 175/80D 13 LRC 5H	2050	84"	16'-17"*	3x3	67"	12	2"	Optional
VR-2250	St 185/80D 13 LRD 5H	2250	84"	17'-18"*	3x3	67"	16	2"	Optional
VR-2450	St 205/75D 14 LRC 5H	2450	88"	17'-18.5"*	3x3	67"	16	2"	Optional
SINGLE AXLE ROLLER 2650-3350 Load Capacity									
VR-2650	St 205/75D 14 LRC 5H	2650	102"	18'-19"*	3x5	84"	20	2"	Optional
VR-2850S	St 205/75D 15 LRC 5H	2850	102"	19'-20"*	3x5	84"	20	2"	Optional
VR-2850	St 205/75D 15 LRC 5H	2850	102"	20'-21"*	3x5	84"	20	2"	Optional
VR-3050S	St 215/75D 14 LRC 5H	3050	102"	18'-20"*	3x5	84"	20	2"	Standard
VR-3150	St 215/75D 14 LRC 5H	3150	102"	20'-21"*	3x5	84"	20	2"	Standard
VR-3350	St 225/75D 15 LRD 6H	3350	102"	20'-21"*	3x5	84"	20	2"	Standard
TANDEM AXLE ROLLER 3650-7950 Load Capacity									
VRT-3650S	St 205/75D 14 LRC 5H	3650	102"	18'-20"*	3x5	84"	20	2"	Standard-1
VRT-3750	St 205/75D 14 LRC 5H	3750	102"	21'-23"*	3x5	84"	20	2"	Standard-1
VRT-4250	St 205/75D 14 LRC 5H	4250	102"	21'-23"*	3x5	84"	24	2"	Standard-1
VRT-4750	St 205/75D 14 LRC 5H	4750	102"	21'-23"*	3x5	84"	28	2"	Standard-1
VRT-5250	St 205/75D 15 LRC 5H	5250	102"	21'-23"*	3x5	84"	32	2"	Standard-1
VRT-5650	St 205/75D 15 LRC 5H	5650	102"	21'-23"*	3x5	84"	32	2"	Standard-1
VRT-5950	St 225/75D 15 LRD 5H	5950	102"	24'-25"*	3x5	84"	44	2" (8,000 lb. ball)	Standard-1
VRT-6450	St 225/75D 15 LRD 6H	6450	102"	25'-26"*	3x5	84"	52	2" (8,000 lb. ball)	Standard-1
VRT-7450	St 225/75D 15 LRD 6H	7450	102"	25'-27"*	3x5	84"	60	2 5/16"	Standard-1
VRT-7950	St 225/75D 15 LRD 6H	7950	102"	25'-27"*	3x5	84"	64	2 5/16"	Standard-1
TRIPLE AXLE ROLLER 8650-10850 Load Capacity									
VRT-8650	St 205/75D 14 LRC 5H	8650	102"	27'-28"*	3x5	84"	64	2 5/16"	Standard-2
VRT-9250	St 225/75D 15 LRD 6H	9250	102"	28'-30"*	3x5	84"	64	2 5/16"	Standard-2
VRT-10850	St 225/75D 15 LRD 6H	10,850	102"	29'-31"*	3x5	84"	80	2 5/16"	Standard-2

Bunk Trailers

Ranked highest for performance, Venture bunk trailers are suggested for boaters who load and launch less frequently. They are good for boaters who store their boats and provide efficient support for the hull. There is also less maintenance necessary for bunk trailers. They are used best for cored hulls as well as boats with less glass.

Model	Tire Size	Load Cap.	Overall Width	Boat Lgth	Frame Size	Between Fender Width	Coupler Size	Brakes & Tongue Jack
SINGLE AXLE BUNK 1000-2400 Load Capacity								
VB-1000	4.80 x 12 LRC 4H	1000	62"	12'-14"*	2x3	48"	2"	Optional
VB-1300	4.80 x 12 LRC 4H	1300	62"	14'-15"*	2x3	48"	2"	Optional
VB-1500	5.30 x 12 LRC 5H	1500	78"	14'-15"*	2x3	60"	2"	Optional
VB-1800	5.30 x 12 LRD 5H	1800	78"	15'-16"*	2x3	60"	2"	Optional
VB-2000	St 175/80D 13 LRC 5H	2000	84"	16'-17"*	3x3	67"	2"	Optional
VB-2200	St 185/80D 13 LRD 5H	2200	84"	17'-18"*	3x3	67"	2"	Optional
VB-2400	St 205/75D 14 LRC 5H	2400	88"	17'-18.5"*	3x3	67"	2"	Optional
SINGLE AXLE BUNK 2600-3300 Load Capacity								
VB-2600	St 205/75D 14 LRC 5H	2600	102"	18'-19"*	3x5	84"	2"	Optional
VB-2800S	St 205/75D 15 LRC 5H	2800	102"	18'-20"*	3x5	84"	2"	Optional
VB-2800	St 205/75D 15 LRC 5H	2800	102"	20'-21"*	3x5	84"	2"	Optional
VB-3000S	St 215/75D 14 LRC 5H	3000	102"	18'-20"*	3x5	84"	2"	Standard
VB-3100	St 215/75D 14 LRC 5H	3100	102"	20'-21"*	3x5	84"	2"	Standard
VB-3300	St 225/75D 15 LRD 6H	3300	102"	20'-21"*	3x5	84"	2"	Standard
TANDEM AXLE BUNK 3600-7900 Load Capacity								
VBT-3600S	St 205/75D 14 LRC 5H	3600	102"	18'-20"*	3x5	84"	2"	Standard-1
VBT-3700	St 205/75D 14 LRC 5H	3700	102"	21'-23"*	3x5	84"	2"	Standard-1
VBT-4200	St 205/75D 14 LRC 5H	4200	102"	21'-23"*	3x5	84"	2"	Standard-1
VBT-4700	St 205/75D 14 LRC 5H	4700	102"	21'-23"*	3x5	84"	2"	Standard-1
VBT-5200	St 205/75D 15 LRC 5H	5200	102"	21'-23"*	3x5	84"	2"	Standard-1
VBT-5600	St 205/75D 15 LRC 5H	5600	102"	21'-23"*	3x5	84"	2"	Standard-1
VBT-5900	St 225/75D 15 LRD 5H	5900	102"	24'-25"*	3x5	84"	2" (8,000 lb. ball)	Standard-1
VBT-6400	St 225/75D 15 LRD 6H	6400	102"	25'-26"*	3x5	84"	2" (8,000 lb. ball)	Standard-1
VBT-7400	St 225/75D 15 LRD 6H	7400	102"	25'-27"*	3x5	84"	2 5/16"	Standard-1
VBT-7900	St 225/75D 15 LRD 6H	7900	102"	25'-27"*	3x5	84"	2 5/16"	Standard-1
TRIPLE AXLE BUNK 8600-10800 Load Capacity								
VBT-8600	St 205/75D 14 LRC 5H	8600	102"	27'-28"*	3x5	84"	2 5/16"	Standard-2
VBT-9200	St 225/75D 15 LRD 6H	9200	102"	28'-30"*	3x5	84"	2 5/16"	Standard-2
VBT-10800	St 225/75D 15 LRD 6H	10,800	102"	29'-31"*	3x5	84"	2 5/16"	Standard-2

Aluminum

Venture aluminum trailers are easy to load and launch any type of trailer. Aluminum trailers have many advantages including accessible maintenance, durability, and they are sold at an affordable cost.

Model	Tire Size	Load Cap.	Boat Length	Coupler Size	Brakes & Tongue Jack	
SINGLE AXLE BUNK 2425-3325 Load Capacity						
VAB-2425	ST185/80D 14 LRD 5H	2425	16'-18"*	2"	Optional	
VAB-2625	ST205/75D 14 LRC 5H	2625	17'-19"*	2"	Optional	
VAB-2825	ST205/75D 14 LRC 5H	2825	18'-20"*	2"	Optional	
VAB-3025	ST215/75D 14 LRC 5H	3025	18'-20"*	2"	Standard 1	
VAB-3325	ST225/75D 15 LRD 6H	3325	20'-22"*	2"	Standard 1	
TANDEM AXLE BUNK 3625-8025 Load Capacity						
VATB-3625	ST205/75D 14 LRC 5H	3625	18'-20"*	2"	Standard 1	
VATB-4225	ST205/75D 14 LRC 5H	4225	21'-22"*	2"	Standard 1	
VATB-5225	ST205/75D 14 LRC 5H	5225	21'-22"*	2"	Standard 1	
VATB-5925	ST205/75D 14 LRC 5H	5925	23'-24"*	2"	Standard 1	
VATB-6425	ST225/75D 15 LRD 6H	6425	24'-25"*	2" (8,000 lb. ball)	Standard 1	
VATB-7225	ST225/75D 15 LRD 6H	7225	25'-26"*	2 5/16"	Standard 1	
VATB-8025	ST225/75D 15 LRD 6H	8025	25'-26"*	2 5/16"	Standard 1	
VATB-8725	ST225/75D 15 LRD 6H	8725	27'-29"*	2 5/16"	Standard 1	
TRIPLE AXLE BUNK 8625-18025 Load Capacity						
VATB-9625	ST225/75D 15 LRD 6H	9625	27'-29"*	2 5/16"	Standard 2	
VATB-10625	ST225/75D 15 LRD 6H	10625	27'-29"*	2 5/16"	Standard 2	
VATB-12625	ST225/75D 15 LRD 6H	12625	29'-32"*	2 5/16"	Standard 3	
VATB-15025	ST235/80R 16 LRE 8H	15025	32'-36"*	2 5/16"	Standard 3	
VATB-18025	ST235/80R 16 LRE 8H	18025	32'-36"*	2 5/16"	Standard 3	
SINGLE AXLE ROLLER 2425-3325 Load Capacity						
Model	Tire Size	Load Cap.	Boat Length	# Rollers	Coupler Size	Brakes & Tongue
VAR-2425	ST185/80D 13 LRD 5H	2425	16'-18"*	16	2"	Optional
VAR-2825	ST205/75D 14 LRC 5H	2825	18'-20"*	20	2"	Optional
VAR-3025	ST215/75D 14 LRD 5H	3025	18'-20"*	20	2"	Standard 1
VAR-3325	ST225/75D 15 LRD 6H	3325	20'-22"*	20	2"	Standard 1
TANDEM AXLE ROLLER 3625-6425 Load Capacity						
VATR-3625	ST205/75D 14 LRC 5H	3625	18'-20"*	20	2"	Standard 1
VATR-4225	ST205/75D 14 LRC 5H	4225	21'-22"*	24	2"	Standard 1
VATR-5225	ST205/75D 14 LRC 5H	5225	21'-22"*	28	2"	Standard 1
VATR-6025	ST205/75D 15 LRC 5H	6025	23'-24"*	44	2" (8,000 lb. ball)	Standard 1
VATR-6425	ST225/75D 15 LRD 5H	6425	24'-25"*	44	2" (8,000 lb. ball)	Standard 1

Skiff Trailers

Venture skiffs are advocated for use of small boats. They are best used for lightweight boats such as sailboats.

Model	Tire Size	Load	Overall	Boat	Coupler	Brakes & Tongue	# Of
-------	-----------	------	---------	------	---------	-----------------	------

ALUMINUM SKIFF 2500-4200 Load Capacity

VASK-2100	ST175/80D 13 LRC 5H	2100	84"	15'-17'*	2"	Optional	1
VASK-2300	ST185/80D 13 LRD 5H	2300	84"	16'-18'*	2"	Optional	1
VASK-2500	ST185/80D 13 LRD 5H	2500	102"	17'-19'*	2"	Optional	1
VASK-2800	ST205/75D 14 LRC 5H	2800	102"	18'-21'*	2"	Optional	1
VASK-3200	ST225/75D 15 LRD 5H	3200	102"	19'-21'*	2"	Standard 1	1
VASK-4200S	ST205/75D 14 LRC 5H	4200	102"	21'-22'*	2"	Standard 1	2
VASK-4200	ST205/75D 14 LRC 5H	4200	102"	22'-23'*	2"	Standard 1	2

Model	Tire Size	Load Cap.	Overall Width	Boat Length	Frame Size	Coupler Size	Brakes & Tongue Jack	# Of Axels
-------	-----------	-----------	---------------	-------------	------------	--------------	----------------------	------------

GALVANIZED STEEL SKIFF 1600-2400 Load Capacity

VSK-1600	20.5x8.0x10 LRC 5H	1600	84"	15'-16'*	3x3	2"	Optional	1
VSK-1800	ST175/80D 13 LRC 5H	1800	84"	17'-18'*	3x3	2"	Optional	1
VSK-2400	ST185/80D 13 LRD 5H	2400	84"	19'-21'*	3x3	2"	Optional	1

Watercraft Trailers

Seadoo owners prefer Venture Water Vehicle Trailers. Single or tandem, our trailers help making load and launch easy.

Model	Tire Size	Load	Overall	Boat	Frame	Coupler	Tongue
-------	-----------	------	---------	------	-------	---------	--------

SINGLE AXLE WATERCRAFT 1200-2000 Load Capacity

VW-1200	4.80 x 12 LRC 4H	1200	62"	2/3 Seater	2x3	2"	Optional
VW-2000	20.5 x 8.0 x 10 LRD 5H	2000	102"	Double	3x3	2"	Optional

Pontoon Trailers

Pontoon boat trailers are conveniently used for activities on protected waters. Venture's stable platform design gives your boat extra support during transport.

Model	Tire Size	Load Cap.	Overall Width	Boat Length	Frame Size	Coupler Size	Brakes & Tongue Jack
SINGLE AXLE PONTOON 2000-2400 Load Capacity							
VP-20-20 E	20.5x8.0x10 LRD	2000	102"	18'-20'*	3x4	2"	Optional
VP-24-20 E	20.5x8.0x10 LRD	2000	102"	22'-24'*	3x4	2"	Optional
VP-20-24 E	20.5x8.0x10 LRE	2400	102"	18'-20'*	3x4	2"	Optional
VP-24-24 E	20.5x8.0x10 LRE	2400	102"	22'-24'*	3x4	2"	Optional
TANDEM AXLE PONTOON 3000-4000 Load Capacity							
VPT-24-30 E	5.30x12 LRC	3000	102"	23'-24'*	3x4	2"	Standard-1
VPT-26-30 E	5.30x12 LRC	3000	102"	24'-26'*	3x4	2"	Standard-1
VPT-26-40 E	20.5x8.0x10 LRD	4000	102"	24'-26'*	3x4	2"	Standard-1
Model	Tire Size	Load Cap.	Overall Width	Boat Length	Frame Size	Coupler Size	Brakes & Tongue Jack
SINGLE AXLE PONTOON 2000-2400 Load Capacity							
VP-20-20 TRI	20.5x8.0x10 LRD	2000	102"	18'-20'*	3x4	2"	Optional
VP-24-20 TRI	20.5x8.0x10 LRD	2000	102"	22'-24'*	3x4	2"	Optional
VP-20-24 TRI	20.5x8.0x10 LRE	2400	102"	18'-20'*	3x4	2"	Optional
VP-24-24 TRI	20.5x8.0x10 LRE	2400	102"	22'-24'*	3x4	2"	Optional
TANDEM AXLE PONTOON 3000-4000 Load Capacity							
VPT-24-30 TRI	5.30x12 LRC	3000	102"	23'-24'*	3x4	2"	Standard-1
VPT-26-30 TRI	5.30x12 LRC	3000	102"	24'-26'*	3x4	2"	Standard-1
VPT-26-40 TRI	20.5x8.0x10 LRD	4000	102"	24'-26'*	3x4	2"	Standard-1