



ARRANGEMENTS



**Standard
Flybridge
Arrangement**



**Standard
Upper Deck
Arrangement**



**Optional
Upper Deck Arrangement
without Helm Station**



**Standard
Three-Stateroom / Three-Head
Arrangement**



**Optional
Four-Stateroom / Three-Head
Arrangement**



SPECIFICATIONS

Length Overall (B)	64'10"	19.76 meters
Beam	18'3"	5.56 meters
Draft (C)	4'8"	1.42 meters
Freeboard Forward (C)	6'10"	2.08 meters
Freeboard Aft (C)	3'8"	1.12 meters
Headroom Most Areas	6'6"	1.98 meters
Freshwater Capacity (C)	265 gallons	1,003 liters
Fuel Capacity (C)	1,515 gallons	5,734 liters
Holding Capacity (C)	95 gallons	359 liters
Weight Displacement (C)	116,700 pounds	52,934 kilos
Height Above Waterline to:		
• Top of Windshield (C)	15'7"	4.75 meters
• Top of Arch (C)	18'10"	5.74 meters
Waterline Length	55'9"	16.99 meters

ENGINE OPTIONS

Twin CAT C18 Diesel Engines	1000 BHP
Twin CAT C32 Diesel Engines	1550 BHP
Twin CAT C32 Diesel Engines	1650 BHP



Exterior Finish/Construction

- Isophthalic gelcoat, exterior layer, white
- Blister resistant vinylester resin in hull bottom skin coat
- Hull and superstructure linear polyester/polyurethane coating
- Polymer/copper based anti-fouling bottom paint
- Boot stripe, linear polyester/polyurethane coating
- Decks, non-skid surface, polyurethane paint with polymeric beads
- Solid fiberglass hull bottom
- Hull sides and superstructure laminated with PVC foam core
- Fiberglass stringers
- Steel laminated in stringers at key locations to bolt engine mounts
- Engine room bulkheads and decks of resin-infused composite construction using PVC foam core with layers of fiberglass laminate on each side

Hardware and Miscellaneous

- Wood bulkheads, cabinetry and trim with a satin or high-gloss polyester finish in cherry or African mahogany
- All hardware polished chrome with brushed chrome in galley
- Welded and polished stainless-steel anchor chute and roller
- 75-pound plow anchor, anchor line and deck hawse pipe
- Windlass, Maxwell RC10 with 25 feet of acculoy hot dipped galvanized chain and 300 feet of rope with deck mounted control switches
- Dual prop bow thruster, 16hp hydraulic
- Four polished stainless-steel springline cleats with chafing strips, through bolted in aluminum backing plates
- Polished stainless-steel bow cleats, through bolted in aluminum backing plates
- Polished stainless-steel stern cleats, through bolted in aluminum backing plates
- Welded and polished stainless-steel rails on bow, side-deck and flybridge, drilled and tapped in aluminum backing plates
- Fog bell
- Dual air horns
- Zincs on rudders and shafts
- Stern staffs with ensign
- Black braided mooring lines (6)

- Alloy 22 high-strength propeller shafts, 3.5-inch
- Manganese bronze dripless rudder seals
- Dripless shaft seals
- Life jackets (8)
- Life ring
- Portable "drychem" fire extinguishers (6), U.L. approved type in compliance with United States Coast Guard and ABYC standards
- Stainless-steel trim tabs
- Integral manganese bronze struts
- Stainless-steel rudders
- 7-blade propellers, Nibral high performance
- MarQuipt sea ladder with storage brackets
- Walk around side decks
- Sunpad on bow deck
- Davit, 1100 pound, fully hydraulic
- Holding tank with sewage pump and overboard discharge
- Black fenders (3)
- Deck plates for fuel and water fills and waste pump-out
- Heavy duty engine couplings
- Engine and generator exhaust exits through hull side near transom

Engine Compartment and Bilge

- Water manifold with centralized shut-off valve for sinks and showers
- Pultruded fiberglass ruddershelf with stainless-steel rudder tie bar
- AC fluorescent lights
- DC lights
- DC ventilation blower
- Twin diesel, freshwater-cooled main engines with electrically controlled marine gears, neutral interlocks, exhaust silencers, engine hour meters, alternators, fuel filters and seawater strainers
- FM200 fixed fire extinguishing system for engine compartment with automatic and remote manual controls, plus audible and visual discharge signals
- One 21.5kW freshwater-cooled Electronic Quiet Diesel Onan generator(D) with shock mounts, sound enclosure, seawater strainer, remote start, fuel/water separator, hour meter and water lift muffler
- Fiberglass air intake system for engine room and engine combustion air with baffling and filters to minimize water intrusion
- Polyethylene water lines
- Electric fuel transfer system with filtration and dry tank protection for pump
- Freshwater fill hose for engines and generator
- AC compressed air system with air line and regulator
- Dockside water inlet with pressure regulating valve and Hatteras patented quick disconnect
- 24-volt DC bilge and sump pumps: five at 2000 gph and three at 3700 gph, with heavy-duty float switches and protective guards
- Bronze/chrome ball-valves through-bolted in solid fiberglass on all underwater through hull fittings with electrical bonding throughout
- Pressurized 230 volt AC freshwater pump
- U.L. Marine listed fiberglass fuel tanks constructed with fire retardant resin with bronze fittings and coated with fire retardant paint
- Fiberglass water tanks, constructed with bronze fittings and materials which comply with the requirements of Title 21 for food and drugs.
- Sewage holding tank with 24 volt DC sewage pump, plumbed for dockside pump-out with ¼ full display and alarm as part of systems monitor programmable logic controller
- U.L. Marine listed fuel filter/water separator, generator
- Sealed shower sump, one each
- U.L. Marine approved fuel filters/water separators, engines
- Electric fuel priming pumps, 24 volt DC, engines
- Painted polyurethane engine room and bilges
- Air conditioning compressors and pumps
- United States Coast Guard type A1 U.L. Marine approved fuel lines
- Discharge sea chests
- 1" stainless-steel steering tie bar with pivoting self-aligning ball joint connection at all cylinder and tie bar connections
- Insulation in deck
- Pick-up sea chests
- Digital monitoring for main engines in battery panel
- Start and stop switches and hour meter
- Rubber deck mat between engines

Electrical Systems

- 230 volt AC 30 gallon electric water heater
- Two 24 volt banks of heavy-duty, 12 volt marine batteries (4) mounted in fire retardant fiberglass boxes

Electrical Systems *(Continued)*

- U.L. 1426 listed boat cable, tin coated with insulation
- Gel/lead acid compatible 240 volt automatic programmable battery charger, 50/60Hz
- Automatic battery paralleling system with switch at control console
- Two 240 volt, 50 amp, transformer connected retractable shore cords with over-current protection (sport deck)
- AC and DC lights and fixtures
- Battery control panel with fuses and isolation switches
- DC electronics panel with magnetic circuit breakers (Lower helm)
- AC and DC distribution panels with magnetic circuit breakers
- AC switching panel with source selector switches, digital volt meter, ammeter, frequency meter, generator start/stop controls, voltage boost tap switch and interlock selector breakers
- Navigation lights, U.L. certified to United States Coast Guard and ABYC specifications
- Ground fault protection on AC receptacles and lighting circuits
- Air conditioning, 76,000 BTU, with reverse-cycle heating, with A/C compressors, individually controlled by SMX controls in each compartment
- TV antenna, omni-directional

Flybridge and Bridge Deck

- 273 square foot flybridge including 102 square foot boat deck
- Systems monitor with programmable logic controller read-out, visual and audible signals for exhaust temperature, alternator, battery voltage, high bilge water, fire warning in engine compartment, fire extinguisher discharge in engine room, AC power loss, smoke detectors, carbon monoxide detectors, and holding tank ¾ full monitor
- Molded fiberglass bridge
- Icom VHF, Furuno RD30 depth and temp
- Welded and polished stainless-steel grab rails and stanchions
- L-shaped lounge with vinyl-covered polyfoam cushions, covers and storage below, port, with access to boat deck
- Tinted acrylic windshield

- Control station with all necessary switches and dimmable lighted instruments
- Painted (polyurethane) aluminum radar arch with masthead light and anchor light
- Compass with dimmable light
- Single-lever clutch and throttle controls (electronic) with engine synchronization
- Hydraulic power assisted steering
- Adjustable helmsman and companion seats with covers (Pompanette)
- Hinged door to galley
- DC AM/FM stereo receiver with CD player and speakers
- Dry bar with refrigerator, storage and molded countertop
- Welded and polished stainless-steel stairs from pilothouse to bridge
- Molded-in stairs to aft deck
- DC low level lights
- Neutral interlock switches allowing engine to start in neutral only

Lower Helm

- Systems monitor with programmable logic controller read-out, visual and audible signals for exhaust temperature, alternator, battery voltage, high bilge water, fire warning in engine compartment, fire extinguisher discharge in engine room, AC power loss, smoke detectors, carbon monoxide detectors, and holding tank ¾ full monitor
- Control station with all necessary switches and dimmable lighted instruments
- Integrated controls (electronic) with emergency back-up and engine synchronization
- Compass with dimmable light
- Hydraulic power assisted steering
- Intermittent electric windshield wipers/washers with controls
- Electric defogger
- Icom VHF, Furuno RD30 depth and temp
- Fuel level gauges

Aft Deck

- Molded fiberglass with non-skid sole
- Molded bench seating with vinyl covered polyfoam cushions and cover
- Fiberglass stairwell from aft deck to bridge deck with storage below
- Molded fiberglass steps with lights to sport deck
- Chain gate from aft deck to steps

- Welded and polished stainless-steel three panel door (one sliding panel) to deckhouse
- Amplifier, speakers, and volume control integrated with Bose salon stereo
- Hardtop
- AC duplex outlet
- AC lighting in hardtop
- Welded and polished stainless-steel handrails and molded fiberglass steps to side decks
- Access hatch to utility and engine compartment
- Aft deck table of solid-surface material

Sport Deck

- Molded fiberglass with non-skid sole
- Freshwater wash down outlet with hose connection and Hatteras patented quick disconnect
- Welded and polished stainless-steel railing
- Molded-in fiberglass steps with DC lights to aft deck
- Pop-up cleats (2)
- Swim platform with re-boarding ladder
- Transom door access to utility room

Galley

- Amtico vinyl-strip flooring
- Padded panel headliner (installed on track system for service access)
- Safety glass
- Steps with lights to lower companionway
- Welded and polished stainless-steel steps to flybridge
- Microwave/convection oven
- AC and DC lights and fixtures
- AC dimmable lights
- AC duplex outlets
- Genuine wood inserts to match interior finish on appliance fascia
- Amplifier, speakers, and volume control integrated with Bose salon stereo
- U-shaped lounge with storage underneath and solid-surface table with stainless-steel pedestal
- Pantograph door to starboard side deck with lock
- Solid-surface countertops with sink and storage cabinets made of finished wood
- Undercounter refrigerator and freezer drawer units with icemaker
- AC two-burner ceramic cooktop
- One-half hp continuous feed garbage disposal

- SMX HVAC compartment controlled
- Storage drawers forward starboard side
- Storage locker with light
- Water level gauge
- Upper level cabinets, inboard

Salon

- Carpeting
- Padded panel headliner (installed on track system for service access)
- Fluted wood valances and duette blinds in recessed pockets
- Welded and polished stainless-steel three panel door (one sliding panel) to aft deck
- Polished stainless-steel threshold
- Steps to galley/pilothouse
- 36" LCD TV with omni-directional antenna
- Bose Lifestyle 35 home theater with AM/FM, CD/DVD, and surround sound speakers
- Fixed frameless windows with tinted safety glass
- AC and DC lights and fixtures
- AC dimmable lights
- AC duplex outlets
- Custom sofa with storage
- Throw pillows
- Air conditioning dispersed through decorative valances
- DC low level lighting behind salon valances, port and starboard
- Two club chairs
- Carbon monoxide detector
- Smoke detector
- SMX HVAC compartment controlled

Companionway

- Carpeting
- Padded panel headliner (installed on track system for service access)
- Padded panels on hullside(s) and bulkhead(s) (installed on track system for service access)
- Flush panel door with door stop to master stateroom, guest staterooms and guest head
- Lighted stairway to pilothouse/galley
- DC light fixtures
- Washer/dryer

Master Stateroom

- Carpeting
- Padded panel headliner (installed on track system for service access)
- Padded panels on hullside(s) and bulkhead(s) (installed on track system for service access)
- King-sized tapered berth with upholstered headboard
- Upholstered berth base
- Polyfoam mattress, spread, throw pillows, pillows, pillow shams, mattress pad and sheets(E)
- Twin cedar-lined wardrobes with doors and automatic lights
- Nightstands with drawers
- Dressers with drawers, port and starboard
- 19" LCD TV
- Bose 3-2-1 GS with AM/FM and DVD/CD w/speakers
- Full-length mirror
- AC and DC lights and fixtures
- AC dimmable lights
- DC low level lights under berth
- AC duplex outlets
- Private access to head
- Smoke detector
- Carbon monoxide detector
- Fluted wood valance with fixed Roman shades and duettes
- Air conditioning dispersed through decorative fluted wood cornice, port and starboard
- SMX HVAC compartment controlled
- Portlight, port and starboard

Bow Guest Stateroom

- Carpeting
- Padded panel headliner (installed on track system for service access)
- Padded panels on hullside(s) and bulkhead(s) (installed on track system for service access)
- Queen-sized tapered berth with upholstered headboard and cedar-lined storage underneath accessed via pneumatic cylinders
- Upholstered berth base
- Polyfoam mattress, spread, throw pillows, pillows, pillow shams, mattress pad and sheets(E)
- Cedar-lined hanging locker with door and automatic light, port and starboard

- Nightstands, port and starboard
- DC AM/FM stereo receiver with CD player and speakers
- Full-length mirror
- AC and DC lights and fixtures
- DC low level lights under berth
- AC duplex outlets
- Private access to head
- Smoke detector
- Carbon monoxide detector
- Air conditioning dispersed through decorative fluted wood valances, port and starboard
- SMX HVAC compartment controlled
- Screened overhead hatch with privacy cover

Port Guest Stateroom

- Carpeting
- Padded panel headliner (installed on track system for service access)
- Padded panels on hullside(s) and bulkhead(s) (installed on track system for service access)
- Side by side twin berths with storage under outboard berth
- Polyfoam mattresses, spreads, throw pillows, pillows, pillow shams, mattress pads and sheets(E)
- Cedar-lined hanging locker with door and automatic light
- Nightstand with drawers
- Full-length mirror
- AC and DC lights and fixtures
- AC duplex outlet
- Smoke detector
- Carbon monoxide detector
- Air conditioning dispersed through fluted wood valance
- SMX HVAC compartment controlled

Optional Fourth Stateroom (F)

- Carpeting
- Padded panel headliner (installed on track system for service access)
- Padded panels on hullside(s) and bulkhead(s) (installed on track system for service access)
- Upper and lower berths with storage under lower berth
- Upholstered berth base
- Polyfoam mattresses, spreads, pillows, mattress pads and sheets(E)
- Cedar-lined hanging locker with light

- Full-length mirror
- AC and DC lights and fixtures
- AC duplex outlet
- Smoke detector
- Carbon monoxide detector
- SMX HVAC bow compartment controlled

Master Head

- Amtico vinyl-strip flooring
- Padded panel headliner (installed on track system for service access)
- Wallcovering
- solid-surface countertop with backsplash, sidesplash and integral sink
- Hardwood baseboards
- Fiberglass tub with shower, door and automatic sump pump
- Storage cabinet with mirror
- Base cabinet to match interior finish with storage
- Towel bar
- Freshwater toilet
- 120 volt AC air freshener blower
- AC and DC lights and fixtures
- DC low level lights under toe kicks
- AC duplex outlet
- Plexi-mirror around forward cabinet
- Air conditioning vent
- Holding tank ¾ full indicator light

Guest Heads

- Amtico vinyl-strip flooring
- Padded panel headliner (installed on track system for service access)
- Wallcovering
- solid-surface backsplash, sidesplash and countertop with integral sink
- Hardwood baseboards
- Stall shower with seat, sliding door and automatic sump pump
- Storage cabinet with mirror
- Base cabinet to match interior finish with storage
- Towel bar
- Freshwater toilet
- 120 volt AC air freshener blower
- AC and DC lights and fixtures
- DC low level lights under toe kicks
- AC duplex outlet
- Plexi-mirror around upper cabinet
- Air conditioning vent
- Holding tank ¾ full indicator light

Storage/Utility Room

- Welded and polishedstainless-steel ladder to aft deck
- Access door to engine room
- Transom door to swim platform

Footnotes

(A) Right is reserved to make changes at any time, without notice, in prices, material, specifications and equipment. Orders are accepted subject to prices prevailing at time of shipment. Orders requesting any material and/or equipment which differ from that selected by Hatteras as standard or optional for this model will be considered a custom change and will require additional charges. Prices shown for many options may apply only if ordered prior to start of production. Once production begins, orders for such options may require additional charges due to non-standard installation requirements and/or lead times. In order to show equipment size and location, line drawing may include some optional items. Specifications, standard equipment and optional equipment effective with boats sold at August 1, 2008 through July 31, 2009 Hatteras Base Prices.

(B) Length overall does not include the optional swim platform or bow pulpit.

(C) Weight, draft, and freeboard are based on an estimate of model's displacement with largest engines available and all tanks filled. Heights are estimated with largest engines and all tanks empty. Actual figures will vary depending on production tolerances, equipment, supplies and stores on board, as well as operational and sea conditions. Capacities of tanks are estimated to be total capacity of all tanks normally furnished in this model. Usable capacities will vary depending upon conditions.

(D) Generator is not intended to supply power for all standard and optional accessories simultaneously. Load must be limited to generator output rating.

(E) One set of sheets includes: one bottom sheet, one top sheet, pillowcase(s).

(F) Option must be ordered prior to start of production. Price shown reflects cost of scheduled installation requirements. A late request for this option will require an additional charge.

